

Reynoclad®




TECHNICAL DATA SHEET

Profiled Aluminum 7.2" Rib Panel

Profiled Aluminum 7.2" Rib Panel

7.2" Rib is an exposed fastener panel that is useful for projects with high wind load requirements and longer spans. Contact a Hoover Architectural Solutions product representative for specific load span requirements and for available product finishes.



MATERIAL SPECIFICATIONS

3000 Series Alloy in compliance with the Aluminum Association Composition Specifications and conforming to ASTM B209 is standard.

PRODUCT NOTES

- Remove the protective film quickly after installation
- Panels should be laid flat in a dry, indoor environment during storage
- Panels should always be lapped against prevailing winds
- Typical side lap spacing is 18"; consult a professional engineer for specific requirements, as this may not be appropriate for all applications
- Purlin spacing: Maximum - 5' on-center
- Panel Length: Maximum 20' Minimum 5'

PRODUCT INSTALLATION


Install panels plumb, level and straight so it is watertight and without waves or other distortions, allowing for thermal movement considerations. Apply sealant tape or caulking as necessary at flashing and panel joints to prevent water penetration.

PRODUCT MAINTENANCE AND WARRANTY

7.2" Rib panels provide up to a 30 year paint-finish warranty for cracking, chipping, peeling, fading and chalking - providing confidence in a long-lasting application.

To ensure the durability of your panels, use proper care. Remove filings, grease, stains, marks or excess sealants from the panel system to prevent staining. Store panels and flashing in a safe, dry environment.

PROFILED ALUMINUM 7.2" RIB PANEL



PANEL DIMENSIONS

Coverage Width	36"
Rib Pitch	7.2"
Profile Depth	1.5"
Thickness	0.040"
Weight	0.62 lb/ft ²

Hoover Architectural Solutions, LLC

50 Industrial Boulevard
Eastman, Georgia 31023-4129

1.800.841.7774
HOOVERAS.COM

Laws and building and safety codes governing the design and use of HAS's products, and specifically aluminum composite materials, vary widely. It is the responsibility of the Laws and building and safety codes governing the design and use of HAS's products, and specifically aluminum materials, vary widely. It is the responsibility of the owner, the architect, the general contractor, the installer and the fabricator/transformer, consistent with their roles, to determine the appropriate materials for a project in strict conformity to all applicable national, regional and local building codes and regulations.