

Reynobond®



COMPOSITE
MATERIAL



BUILD
BOLDER.

COMPLETE
VERSATILITY
IN EXTERIOR
APPLICATIONS—
WITH REYNOBOND®
COMPOSITE
MATERIAL.


Reynobond® composite panels consist of two coated aluminum sheets that are laminated to both sides of a fire-retardant (FR) core. Flatness, lightweight, minimal expansion, high corrosion and weather resistance are some of the advantages that make it an outstanding product. Please ask for the product datasheet for more information.



VERSATILE AND
EASY TO FABRICATE.

Reynobond® composite panels enable flexibility in fabrication allowing freedom in design for unusual shapes.

- Bending
- Rolling






The Advantages of Reynobond®

Products

- Cost-effective: easy and quick installation and maintenance
- Highly UV and weather resistant
- Warranty up to 30 years
- Easy to fabricate and bend: freedom in design for unusual shapes

Services

- In widths up to 62 in and lengths up to 243 in (contact your local sales representative for longer lengths)
- Flexible and short lead times for standard stocking items



Paint Qualities & Technical Coatings

Good resistance to corrosion, UV and weathering, flexibility required for fabrication, and a wide range of colors are some of the advantages offered by our paint qualities. Finishes come with a warranty up to 30 years.




Colorweld® 500/500XL

High-performing, coil-coated finishes that allow color matching at the highest uniformity and quality. They feature 70% Kynar 500® / Hylar 5000® polyvinylidene fluoride (PVDF) resins with fluoropolymer technology, providing excellent flexibility and film adhesion for forming, with superior resistance to humidity, impact, salt spray, pollution and abrasion. Colorweld® 500/500XL paint is specifically developed for exterior applications including facades, soffits, and other decorative architectural features, making it ideal for both new construction and refurbishment projects.

Design Line™

A high-performance coating engineered specifically for exterior architectural applications, providing a durable and visually refined finish for both new construction and renovation projects. These multi-layer, polymer coatings provide high resistance to aging, UV and corrosion making them an attractive option for large outdoor applications.

Contact a sales or technical representative for additional information at HASTechnicalSales@hoooveras.com.



Wide Range of Colors.

You can find all standard finishes in our color chart:

- **Colorweld® 500/500XL:** Solid, Mica, Metallic
- **Design Line™:** Wood, Mineral, Patina, Stone, Concrete
- **PrismFX™:** Color Shifting
- **Brushed Aluminum:** Natural Brushed, Long Brushed
- **Mirror:** Brite, Bronze, Copper, Gold, Stainless Steel
- **Anodized:** Clear and Tinted

Custom color matching also available.



Technical Data Reynobond® Composite Material

Products Composition		Reynobond® FR
Thickness composite panel		0.157 in - 4mm
Thickness pre-painted aluminum sheet		0.020 in (± 0.002 in) - 0.5 mm (± 0.2 mm)
Alloy & temper		Series 3000
Core		FR
Front side finish		Anti-corrosive treatment plus: COLORWELD® 500/500XL or DURAGLOSS® DL/PFX
Reverse side finish		Washcoat - Other on request
Products Characteristics		
Width		62 in - 1575 mm
Length		243 in - 6172 mm
Weight		1.55 lb/ft² - 7.57 kg/m²
Tolerance in squareness		<0.118 in - < 3 mm
Tolerance in bow		+ 1/8"
Products Performance		
Tensile strength (Rm)	lb/in² - MPa	6.3 ks - 43.90 MPa
Flexural Modulus (Core Yield Shear stress)		176 psi - 1.21 MPa
Stiffness (EI)	lb-in²/in - MPa/cm²	1,133 lb-in²/in² - 1.28x10 ⁴ MPa/cm²
Thermal expansion		0.0288 in/ft OR 2.4 mm/m for a temperature variation of 100°C (212°F)
Temperature resistance		-40°F / +180°F - -40°C / +80°C
Maximum allowable deflection		L/60
Fire classification		
Flame Spread Index	ASTM E84	<25 - <450
Self Ignition Temperature	ASTM D1929	824°F - 440°C

Check local building code for acceptable deflection limits.
Our paint datasheets are also available, please ask for the dedicated datasheet.
The technical data refers to currently available products.

Hoover Architectural Solutions, LLC
50 Industrial Boulevard
Eastman, Georgia 31023-4129

1.800.841.7774
HOOVERAS.COM

Information contained herein or related hereto is intended only for evaluation by technically skilled persons, with any use thereof to be at their independent discretion and risk. Such information is believed to be reliable, but HAS shall have no responsibility or liability for results obtained or damages resulting from such use. HAS grants no license under, and shall have no responsibility or liability for infringement of, any patent or other proprietary right. Nothing in this document should be construed as a warranty or guarantee by HAS, and the only applicable warranties will be those set forth in HAS acknowledgment or in any printed warranty documents issued by HAS. The foregoing may be waived or modified only in writing by an HAS officer.

Disclaimer: Laws and building and safety codes governing the design and use of Hoover Architectural Solutions, LLC's products, and specifically aluminum composite materials, vary widely. It is the responsibility of the owner, the architect, the general contractor, the installer and the fabricator/transformer, consistent with their roles, to determine the appropriate materials for a project in strict conformity to all applicable national, regional and local building codes and regulations. REYNOBOND® FR AND REYNODUAL® HAVE SUCCESSFULLY PASSED US NFPA 285, E84 AND CANADA S134, S102 TESTS AS A PART OF AN ASSEMBLY. ENSURE THE PRODUCT IS USED IN A SYSTEM THAT COMPLIES WITH ALL APPLICABLE REGULATIONS. REYNOBOND® PE IS COMBUSTIBLE; IT COULD CATCH FIRE AND BURN. ANY LABORATORY TESTING INFORMATION PROVIDED BY HOOVER ARCHITECTURAL SOLUTIONS, LLC APPLIES ONLY TO THE PARTICULAR PRODUCT OR ASSEMBLY TESTED AND DOES NOT NECESSARILY REPRESENT HOW PRODUCTS WILL ACTUALLY PERFORM IN USE. REPORTS AND TEST DATA CORRESPONDING TO A PARTICULAR TESTED PRODUCT SAMPLE OR ASSEMBLY ARE NOT A GUARANTEE THAT THE SAME PRODUCT OR ASSEMBLY WOULD ALWAYS ACHIEVE THE SAME TEST RESULT.